

# Safety Data Sheet

## SECTION 1 – IDENTIFICATION

### Name, Address, and Telephone of the Responsible Party

**Dyno Nobel Inc.**

2795 East Cottonwood Parkway, Suite 500

Salt Lake City, Utah 84121

Phone: 801-364-4800 Fax 801-321-6703

E-Mail: [dнна.hse@am.dynonobel.com](mailto:dнна.hse@am.dynonobel.com) [www.dynonobel.com](http://www.dynonobel.com)

**SDS #:** 1052

**Date:** 05/15/2015

Supersedes: 12/15/2011

### Product Identifier

**Product Form:** Mixture

**Product Name:** Bulk Emulsion

### Other Means of Identification

#### Synonyms:

DYNO GOLD<sup>®</sup>

DYNO GOLD<sup>®</sup> LITE

EXTRAMITE 1000

RUG-1 (Canada Only)

TITAN<sup>®</sup> 1000

TITAN<sup>®</sup> 1000 GREEN

TITAN<sup>®</sup> 1000G

TITAN<sup>®</sup> 1000G GREEN

TITAN<sup>®</sup> XL1000

SMS 1116, 1116A, 1126P,

1136P, 1146P

TITAN<sup>®</sup> 2000

TITAN<sup>®</sup> 2000G

TITAN<sup>®</sup> PB 1000

TITAN<sup>®</sup> PB 2000

TITAN<sup>®</sup> PB 2000 HF

TITAN<sup>®</sup> SME 1000

TITAN<sup>®</sup> SME 1000 GREEN

TITAN<sup>®</sup> XL1000 GREEN

TITAN<sup>®</sup> HD

TITAN<sup>®</sup> SME 2000

DX5037

### Intended Use of the Product

Industrial blasting applications as emulsion explosive precursor

### Emergency Telephone Number

FOR 24 HOUR **EMERGENCY**, CALL **CHEMTREC (USA)** 800-424-9300  
**CANUTEC (CANADA)** 613-996-6666

## SECTION 2 – HAZARD(S) IDENTIFICATION

### Classification of the Substance or Mixture

#### Classification (GHS-US)

Ox. Liq. 2

H272

Acute Tox. 4 (Oral)

H302

Skin Irrit. 2

H315

Carc. 2

H351

STOT RE 2

H373

Asp. Tox. 1

H304

Eye Irrit. 2B

H320

#### Label Elements

#### GHS-US Labeling

#### Hazard Pictograms (GHS-US)



GHS03



GHS07



GHS08

#### Signal Word (GHS-US)

: Danger

#### Hazard Statements (GHS-US)

: H272 - May intensify fire; oxidizer

H302 - Harmful if swallowed

H315 - Causes skin irritation

# Safety Data Sheet

H351 - Suspected of causing cancer  
 H373 - May cause damage to organs through prolonged or repeated exposure  
 H304 - May be fatal if swallowed and enters airways  
 H320 - Causes eye irritation

**Precautionary Statements (GHS-US)** :

P201 - Obtain special instructions before use  
 P202 - Do not handle until all safety precautions have been read and understood  
 P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
 P220 - Keep/Store away from clothing, combustible materials, combustibles  
 P221 - Take any precaution to avoid mixing with combustible materials, clothing, combustibles  
 P233 - Keep container tightly closed  
 P260 - Do not breathe dust, fume, mist, spray, vapors  
 P264 - Wash exposed areas thoroughly after handling  
 P270 - Do not eat, drink or smoke when using this product  
 P273 - Avoid release to the environment  
 P280 - Wear protective gloves/protective clothing/eye protection/face protection  
 P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 P302+P352 - IF ON SKIN: Wash with plenty of soap and water  
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 P308+P313 - If exposed or concerned: Get medical advice/attention  
 P332+P313 - If skin irritation occurs: Get medical advice/attention  
 P362 - Take off contaminated clothing and wash before reuse  
 P370+P378 - In case of fire: Use appropriate media to extinguish  
 P403+P235 - Store in a well-ventilated place. Keep cool  
 P405 - Store locked up  
 P501 - Dispose of contents/container according to local, regional, national, and international regulations

**Other Hazards**

**Hazards Not Otherwise Classified (HNOC):** Not available

**Other Hazards:** Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

## SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Mixture			
Name	Product identifier	% (w/w)	Ingredient Classification (GHS-US)
Ammonium nitrate	(CAS No) 6484-52-2	45 - 80	Ox. Sol. 3, H272 Eye Irrit. 2A, H319
Calcium nitrate	(CAS No) 10124-37-5	0.1 - 35	Ox. Sol. 3, H272 Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318
Sodium nitrate	(CAS No) 7631-99-4	0.1 - 18	Ox. Sol. 3, H272 Acute Tox. 4 (Oral), H302 Eye Irrit. 2A, H319
*Fuels, diesel, no. 2	(CAS No) 68476-34-6	0.1 - 10	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332

# Safety Data Sheet

			Skin Irrit. 2, H315 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304
Distillates, petroleum, chemically neutralized light naphthenic	(CAS No) 64742-35-4	0.1 - 6	Asp. Tox. 1, H304

\* This ingredient is not used in GREEN-named products.  
Ingredients, other than those mentioned above, as used in this product are not hazardous as defined under current Department of Labor regulations, or are present in deminimus concentrations (less than 0.1% for carcinogens, less than 1.0% for other hazardous materials).  
Full text of H-phrases: see section 16

## SECTION 4 - FIRST AID MEASURES

### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** If symptoms occur, go into fresh air and ventilate suspected area. Seek medical attention.

**Skin Contact:** Remove contaminated clothing. Wash with soap and water followed by rinsing with water. Seek medical attention if irritation develops or persists. Wash contaminated clothing before reuse.

**Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Seek medical attention immediately.

### Most Important Symptoms and Effects Both Acute and Delayed

**General:** May be harmful if swallowed. May cause eye or skin irritation.

**Inhalation:** May cause respiratory irritation.

**Skin Contact:** May cause skin irritation.

**Eye Contact:** May cause eye irritation.

**Ingestion:** Likely to be harmful if swallowed.

**Chronic Symptoms:** Contains an ingredient which may cause cancer. Causes damage to organs through prolonged or repeated exposure.

### Indication of Any Immediate Medical Attention and Special Treatment Needed

If symptoms occur, seek medical attention.

## SECTION 5 - FIRE-FIGHTING MEASURES

### Extinguishing Media

**Suitable Extinguishing Media:** Do not attempt to fight fires involving explosive materials or emulsion explosive precursors. Evacuate all personnel to a predetermined safe location, no less than 2,500 feet in all directions.

**Unusual Fire and Explosion Hazards:** May explode or detonate under fire conditions. Burning material may produce toxic vapors.

**Unsuitable Extinguishing Media:** Not available

### Special Hazards Arising From the Substance or Mixture

In intense fires the emulsion can detonate from confinement or strong shocks. Evacuation of at least 1 mile is recommended if the emulsion is involved in a fire.

**Fire Hazard:** May intensify fire; oxidizer. Will burn if exposed to heat, and in addition, will accelerate the burning of other combustibles, resulting in more rapid spread of fire.

**Explosion Hazard:** Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. May explode when subjected to fire, supersonic shock or high-energy projectile impact, especially when confined or in large quantities.

**Reactivity:** May cause or intensify fire; oxidizer. May accelerate the burning of other combustible materials.

### Advice for Firefighters

**Precautionary Measures Fire:** DO NOT ATTEMPT TO FIGHT FIRES INVOLVING EXPLOSIVE MATERIALS. Evacuate

# Safety Data Sheet

all personnel to a predetermined safe location, no less than 2,500 feet in all directions. Can explode or detonate under fire conditions. Burning material may produce toxic vapors.

**Firefighting Instructions:** DO NOT ATTEMPT TO FIGHT FIRE. Immediately evacuate all personnel from the area to a safe distance. Guard against re-entry. Thermal decomposition can lead to release of irritating gases and vapors.

**Protection During Firefighting:** When controlling fire before involvement of explosives or explosive precursors, fire-fighters should wear positive pressure self-containing breathing apparatus (SCBA) and full turnout gear.

**Hazardous Combustion Products:** Nitrogen oxides. Carbon oxides (CO, CO<sub>2</sub>). Ammonia.

**Other information:** Do not attempt to fight fires involving explosive materials or emulsion explosive precursors. Evacuate all personnel to a predetermined safe location, no less than 2,500 feet in all directions.

**Reference to Other Sections:** Refer to section 9 for flammability properties.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Avoid all contact with skin, eyes, or clothing. Avoid breathing dust, mist, or spray. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Eliminate every possible source of ignition. Evacuate danger area.

#### For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### For Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Ventilate area.

### Environmental Precautions

Prevent entry to sewers and public waters.

### Methods and Material for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes as necessary to prevent migration and entry into sewers or streams. Do not take up in combustible material such as: saw dust or cellulosic material.

**Methods for Cleaning Up:** Collect spillage for possible reuse. Clean up spills immediately and dispose of waste in accordance with appropriate state, federal and local regulations.

### Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection

## SECTION 7 - HANDLING AND STORAGE

### Precautions for Safe Handling

It is recommended that users of explosives material be familiar with the Institute of Makers of Explosives Safety Library publications.

**Additional Hazards When Processed:** When heated to decomposition, emits toxic fumes. Do not puncture or incinerate containers.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

### Conditions for Safe Storage, Including Any Incompatibilities

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep /store away from combustible materials, extremely high or low temperatures, direct sunlight, ignition sources, incompatible materials.

**Incompatible Materials:** Corrosives, strong acids, strong bases and alkalis.

## SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

#### Exposure Controls

**Appropriate Engineering Controls:** Ensure all national/local regulations are observed. Ensure adequate ventilation, especially in confined areas.

# Safety Data Sheet

**Personal Protective Equipment:** Protective goggles. Gloves. Protective clothing.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical goggles or face shield.

**Skin and Body Protection:** Not available.

**Respiratory Protection:** Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of vapor or mist are expected to exceed exposure limits.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Translucent to opaque viscous liquid.
Odor	: Fuel
Odor Threshold	: Not available
pH	: Not available
Relative Evaporation Rate (butylacetate=1)	: < 1
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: 0.8 - 1.5 g/cc
Solubility	: Water: Nitrate salts are completely soluble, but emulsion dissolution is very slow.
Partition coefficient: n-octanol/water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not sensitive to mechanical impact. May be sensitive to supersonic explosively driven projectile impacts.
Explosion Data – Sensitivity to Static Discharge	: Not sensitive to static discharge.

# Safety Data Sheet

## SECTION 10 - STABILITY AND REACTIVITY

**Reactivity:** May cause or intensify fire. May accelerate the burning of other combustible materials.

**Chemical Stability:** May intensify fire. May explode when subjected to fire, supersonic shock or high-energy projectile impact, especially when confined or in large quantities.

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight. Extremely high temperatures. Heat. Sparks. Overheating. Open flame. Combustible materials. Sources of ignition. Incompatible materials.

**Incompatible Materials:** Corrosives, strong acids, strong bases and alkalis.

**Hazardous Decomposition Products:** Nitrogen oxides. Toxic vapors. Ammonia. Carbon monoxide.

## SECTION 11 - TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects - Product

**Acute Toxicity:** Harmful if swallowed.

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Causes skin irritation.

**Serious Eye Damage/Irritation:** Causes serious eye damage.

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Teratogenicity:** Not available

**Carcinogenicity:** Suspected of causing cancer.

**Specific Target Organ Toxicity (Repeated Exposure):** May cause damage to organs through prolonged or repeated exposure.

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** May cause respiratory irritation.

**Symptoms/Injuries After Skin Contact:** May cause skin irritation.

**Symptoms/Injuries After Eye Contact:** Causes serious eye damage.

**Symptoms/Injuries After Ingestion:** May be harmful if swallowed. May be harmful if swallowed and enters airways.

Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

**Chronic Symptoms:** May cause cancer. Causes damage to organs through prolonged or repeated exposure.

### Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

#### Ammonium nitrate (6484-52-2)

LD50 Oral Rat	2217 mg/kg
---------------	------------

LC50 Inhalation Rat	> 88.8 mg/l/4h
---------------------	----------------

ATE CLP (oral)	2217.000 mg/kg body weight
----------------	----------------------------

#### Sodium nitrate (7631-99-4)

LD50 Oral Rat	1267 mg/kg
---------------	------------

ATE CLP (oral)	1267.000 mg/kg body weight
----------------	----------------------------

#### Fuels, diesel, no. 2 (68476-34-6)

ATE CLP (vapors)	11.000 mg/l/4h
------------------	----------------

#### Distillates, petroleum, chemically neutralized light naphthenic (64742-35-4)

LD50 Oral Rat	> 5000 mg/kg
---------------	--------------

LD50 Dermal Rabbit	> 2000 mg/kg
--------------------	--------------

# Safety Data Sheet

## SECTION 12: ECOLOGICAL INFORMATION

**Toxicity** Not classified

### Sodium nitrate (7631-99-4)

LC50 Fish 1	2000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC 50 Fish 2	994.4 - 1107 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

### Fuels, diesel, no. 2 (68476-34-6)

LC50 Fish 1	35 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
-------------	---

### Calcium nitrate (10124-37-5)

LC50 Fish 1	10000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
-------------	--

### Persistence and Degradability

#### Bulk Emulsion

Persistence and Degradability	Not established.
-------------------------------	------------------

### Sodium nitrate (7631-99-4)

Persistence and Degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

### Bioaccumulative Potential

#### Bulk Emulsion

Bioaccumulative Potential	Not established.
---------------------------	------------------

### Ammonium nitrate (6484-52-2)

BCF fish 1	(no bioaccumulation expected)
Log Pow	-3.1 (at 25 °C)

### Sodium nitrate (7631-99-4)

Log Pow	-3.8 (at 25 °C)
Bioaccumulative Potential	Not expected to bioaccumulate.

**Mobility in Soil** Not available

### Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 13 – DISPOSAL CONSIDERATIONS

**Waste Treatment Methods:** Contact manufacturer for advice on proper disposal methods.

**Waste Disposal Recommendations:** Collect spillage for possible reuse. Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

**Additional Information:** Clean up even minor leaks or spills if possible without unnecessary risk.

## SECTION 14 - TRANSPORT INFORMATION

### 14.1 In Accordance with DOT

Proper Shipping Name	: AMMONIUM NITRATE EMULSION
Hazard Class	: 5.1
Identification Number	: UN3375
Label Codes	: 5.1
Packing Group	: II
ERG Number	: 140



### 14.2 In Accordance with IMDG

Proper Shipping Name	: AMMONIUM NITRATE EMULSION
Hazard Class	: 5.1
Identification Number	: UN3375
Packing Group	: II

# Safety Data Sheet

Label Codes : 5.1  
 EmS-No. (Fire) : F-H  
 EmS-No. (Spillage) : S-Q



#### 14.3 In Accordance with IATA

Proper Shipping Name : AMMONIUM NITRATE EMULSION  
 Identification Number : UN3375  
 Hazard Class : 5  
 Label Codes : 5.1  
 ERG Code (IATA) : 5L



#### 14.4 In Accordance with TDG

No UN number exists for blasting intermediates for Transport Canada (use the following for Canadian shipments)

Proper Shipping Name : EXPLOSIVE, BLASTING, TYPE E  
 Packing Group : II  
 Hazard Class : 1.5D  
 Identification Number : UN0332  
 Label Codes : 1.5D



## SECTION 15 - REGULATORY INFORMATION

### US Federal Regulations

#### Bulk Emulsion

#### SARA Section 311/312 Hazard Classes

Immediate (acute) health hazard  
 Reactive hazard  
 Delayed (chronic) health hazard  
 Fire hazard

#### Ammonium nitrate (6484-52-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Sodium nitrate (7631-99-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Fuels, diesel, no. 2 (68476-34-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Calcium nitrate (10124-37-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Distillates, petroleum, chemically neutralized light naphthenic (64742-35-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### US State Regulations

#### Ammonium nitrate (6484-52-2)

U.S. - Massachusetts - Right To Know List  
 U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
 U.S. - Pennsylvania - RTK (Right to Know) List

#### Sodium nitrate (7631-99-4)

U.S. - Massachusetts - Right To Know List  
 U.S. - Pennsylvania - RTK (Right to Know) List

#### Fuels, diesel, no. 2 (68476-34-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

#### Calcium nitrate (10124-37-5)

U.S. - New Jersey - Right to Know Hazardous Substance List



# Safety Data Sheet

## Canadian Regulations

### Bulk Emulsion

WHMIS Classification      **Note: Explosives are not regulated under WHMIS. They are subject to the regulations of the Explosives Act of Canada.**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision date** : 05/15/2015  
**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### GHS Full Text Phrases:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Ox. Liq. 2	Oxidizing liquids Category 2
Ox. Sol. 3	Oxidizing solids Category 3
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H226	Flammable liquid and vapor
H272	May intensify fire; oxidizer
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

### Party Responsible for the Preparation of This Document

Dyno Nobel Inc.  
2795 East Cottonwood Parkway, Suite 500  
Salt Lake City, Utah 84121  
Phone: 801-364-4800

### Disclaimer

Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, the information contained herein, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. The information contained herein is provided for reference purposes only and is intended only for persons having relevant technical skills. Because conditions and manner of use are outside of our control, the user is responsible for determining the conditions of safe use of the product. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product or information. Under no circumstances shall either Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.

Dyno Nobel SDS

# TITAN<sup>®</sup> XL 1000

## Technical Information



## Gassed Bulk Emulsion



### Product Description

TITAN XL 1000 is a gassed, bulk emulsion made from TITAN 1000 or TITAN 1000 G specifically designed for quarry and open pit mining operations. Transported as an oxidizer, TITAN XL 1000 is formulated to be sensitized during the borehole loading process using Dyno Nobel's innovative chemical gassing and emulsion processing technology. The process used to manufacture TITAN XL 1000 enhances water resistance and detonation performance while improving loading characteristics. Chemical gassing allows the average density of TITAN XL 1000 to be varied as required to optimize its explosive performance for best blast results.

### Application Recommendations

- The minimum cast booster weight recommended to prime TITAN XL 1000 explosive is a 340 g (12 oz) cast booster.
- TITAN XL 1000 can be used in boreholes up to 36 m (120 ft) deep.
- **ALWAYS** double prime when bulk explosive columns exceed 6 m (20 ft). One primer should be positioned near the bottom of the hole and the second near the collar.
- **ALWAYS** ensure primers are securely positioned in the explosive column.
- Do not use detonating cord as downlines with Titan XL 1000 without first consulting your dyno Nobel representative.

## Properties

SDS  
#1052

<b>Density</b> (g/cc) Avg	1.20
The average loading density can be varied from about 1.00 to 1.25 g/cc to best match rock type and application requirements.	
<b>Energy<sup>a</sup></b> (cal/g)	680
(cal/cc)	815
<b>Relative Weight Strength<sup>a,b</sup></b>	0.77
<b>Relative Bulk Strength<sup>a,b</sup></b>	1.13
<b>Velocity<sup>c</sup></b> (m/sec)	5,200
(ft/sec)	17,100
<b>Detonation Pressure<sup>c</sup></b> (Kbars)	81
<b>Gas Volume<sup>a</sup></b> (moles/kg)	45.0
<b>Water Resistance</b>	Excellent
<b>Minimum Diameter</b>	
(mm)	65
(inches)	2.5
<b>Loading Method</b>	Pumped
<b>Fume Class<sup>d</sup></b>	IME1

<sup>a</sup> All Dyno Nobel Inc. energy and gas volume values are calculated using PRODET™, a computer code developed by Dyno Nobel Inc. for its exclusive use. Other computer codes may give different values.

<sup>b</sup> ANFO = 1.00 @ 0.82 g/cc

<sup>c</sup> Confined in 150 mm (6 in) diameter at average density.

<sup>d</sup> Approved for underground use as IME Fume Class 1.

### Hazardous Shipping Description

TITAN XL 1000 is made from TITAN 1000 or TITAN 1000 G bulk emulsion matrix. Refer to the TITAN 1000 Technical Information Sheet for Hazardous Shipping Description information.

# TITAN<sup>®</sup> XL 1000

Technical  
Information



## Transportation, Storage and Handling

- TITAN XL 1000 can be stored for 3 months at temperatures between -18° C and 32° C (0° F and 90° F). Older product should be used first and all storage tanks should be kept clean of residual product.
- Use only pumps which have been approved by Dyno Nobel for 5.1 emulsion matrix transfer. Pump type, pump speed, worn pump parts, repeated repumping and pumping against high hose pressures can increase TITAN 1000 viscosity and decrease shelf life.
- **ALWAYS** monitor emulsion pump performance and check pumps periodically for excessively worn parts. Design storage facilities to minimize repeated pumping.
- Transport, store, handle and use TITAN XL 1000 in compliance with federal, state, provincial and local laws governing bulk oxidizing liquids.

**Product Disclaimer** Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product. Under no circumstances shall Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.

## Dyno Nobel Inc.

2795 East Cottonwood Parkway, Suite 500, Salt Lake City, Utah 84121 USA  
Phone 800-732-7534 Fax 801-328-6452 Web [www.dynonobel.com](http://www.dynonobel.com)

**DYNO**<sup>®</sup>  
Dyno Nobel

Groundbreaking Performance<sup>™</sup>